



Video Conference Camera



s



Record your meeting in full HD



Best device for virtual conference



Easy to setup and mounting option



Comes with optical and digital zoom

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com

Video Conference Camera *****	
Optical Zoom	20x
Digital Zoom	16x
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Lens	f4.4mm ~ 88.5mm, F1.8 ~ F2.8
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Scanning Mode	Progressive
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Vertical Angle of View	34.1 degrees ~ 1.89 degrees
Horizontal Rotation Range	±170 degree
Vertical Rotation Range	Minus 30 degrees ~ Plus 90 degree
Pan Speed Range	1.7 degrees ~ 100 degrees per second
Tilt Speed Range	1.7 degrees ~ 70 degrees per second
Video S/N	≥55dB
Horizontal Angle of View	60.7 degrees ~ 3.36 degrees
H & V Flip	Support
Video System	1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30, 1080p/25
Operate System	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color System	YUV 4:2:2
Video Format USB 3.0	1080P@60fps
Audio on USB	Support
Video	H.265/H.264/MJPEG
Video Stream	Mainstream, Sub Stream
Image Freeze	Support
Number of Preset	255
Preset Accuracy	0.1°
Main Stream Resolution	1920x1080, 1280x720, 1024x576
Sub Stream Resolution	1280x720, 720x576, 320x240
Video Bit Rate	128Kbps ~ 8192Kbps
Bit Rate Type	Variable Rate, Fixed Rate
Frame Rate	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Audio	AAC

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com

Audio Bit Rate	96Kbps, 128Kbps, 256Kbps
Support protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast
Audio Encoding	Device Support AAC audio encoding, better sound quality and smaller bandwidth.
Local Storage	Device Support local storage module, directly recording to local USB flash disk.
Low Light	Device support High SNR of CMOS sensor, even under low illumination conditions, picture can still keep clean and clear.
Remote Control	All the parameters of the camera can be remote controlled by the high-speed communications
Video Output	1xUSB3.0, 1x HDMI, 1x CVBS
Network Interface	1xRJ45: 10M/100M Ethernet Interface
Audio Interface	1-ch: 3.5mm Audio Interface Line In
Communication Interface	1xRS232 In, 1xRS232 Out, 1xRS485
Power Jack	JEITA type (DC IN 12V)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Tripod stand	Yes

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES

Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com