4K PTZ Camera



- AI-Tracking Modes
- Best device for virtual conference
- Easy to setup and mounting option
- Comes with optical and

Video Conferencing Camera : UE-CAM-12	
Sensor	Sony 1/2.8" CMOS Sensor
Optical Zoom	12x
Digital Zoom	8x
AI-Tracking Modes	Presenter Tracking, Auto Framing
Effective Pixels	8.29 MP
Aperture	F1.8 - 3.0
Lens	f=3.4mm ~ 40.9mm
Horizontal Field-of-View	70° ~ 7.6°
Vertical Field-of-View	40° ~ 4.3°
Diagonal Field-of-View	76° ~ 8.7°
Video Format	HDMI: 3840x2160@30/25, 2560x1440@60, 1920x1080@60/50/30/25, 1280x720@60/50 USB: Max to 3840x2160@30
Video Encoding Format	H.264, H.265, MJPEG, YUY2
Video S/N	≥50dB
Input Voltage	DC 12V
Current Consumption	2A (Max)
Power Consumption	24W (Max)
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Digital Noise Reduction	2D and 3D Digital Reduction
Focus	Auto/manual
Exposure	Auto/manual
Horizontal Rotation	350° (-175° to +175°)
Vertical Rotation	180° (-90° to +90°)
Number of presets	User can set up to 255 presets (10 presets on IR remote)
Video Interfaces	HDMI, USB 3.0, RJ45
LAN	10M/100M, Supports PoE IEEE802.3 af
Video Streams	Main Stream: 1920x1080 (Max), Sub Stream: 1280x720 (Max)
Network Protocol	RTSP, RTMP, VISCA Over IP, ONVIF
Control Protocol	VISCA/PELCO-D/PELCO-P
Control Interface	RS232(input), RS485, USB3.0 (UVC1.1), RJ45
Compatible Operating Systems	Windows/Android/Mac OS/Linux

Product image(s) are for illustrative purposes only and may differ from the actual product



UNIVERSAL ENTERPRISES
Mangal Parao, Haldwani (Uttarakhand)
Ph.: 05946-255434, Fax: 05946-252300
Email: universalenterprises111@gmail.com